



INPUT WIRES:  
BLACK & WHITE  
GROUND:  
GREEN

OUTPUT WIRES:  
&  
BLUE & BLUE

## SPECIFICATIONS

1. INPUT IS 120 VAC / 60 HZ.
2. OUTPUT IS 12 VAC UNDER FULL-LOAD CONDITIONS.
3. ENCLOSURE TEMPERATURE DOES NOT EXCEED 65°C IN A 40°C AMBIENT, FULLY LOADED.
4. THE ACTUAL 60VA TRANSFORMER IS ENCAPSULATED IN THE ENCLOSURE.
5. THE TRANSFORMER IS DIMMABLE WITH ALL DIMMERS THAT PROVIDE A SYMMETRICAL FORM OF CURRENT UNDER ANY CONDITION.
6. INPUT LEADS ARE 20AWG, LEAD INSULATION IS PVC 600V  
OUTPUT LEADS ARE 16AWG, LEAD INSULATION IS PVC 300V
7. THE TRANSFORMER HAS TWO AUTO-RESET BREAKERS ON THE SECONDARY SIDE.
8. WIRING COMPARTMENT HAS 2 KNOCKOUTS SIZED FOR 3/4 INCH SCREW CABLE CONNECTORS.
9. THE WIRING COMPARTMENT COVER HAS A REMOVEABLE COVER SECURED WITH A SCREW.
10. THE ENCLOSURE IS RATED NEMA 3R
11. THE TRANSFORMER IS ETL/CSA LISTED
12. WEIGHT: 3.2 lb



### TOKISTAR LIGHTING INC.

1015 E. DISCOVERY LANE  
ANAHEIM, CA 92801  
TEL: 714 772 7005 FAX: 714 772 7014  
email: info@tokistar.com Website: tokistar.com

PART NO. C2-60-12V

60VA TRANSFORMER INPUT: 120VAC / OUTPUT: 12VAC