


Catalog#	LED Spacing	Lens	Length	Power	Weight
GRX-GG-(2700, 3000, 4000)-15D-300	3" (75 mm)	15°	12" (300 mm)	12 Watts	1.1 lb. / 490g
GRX-GG-(2700, 3000, 4000)-15D-600	3" (75 mm)	15°	24" (600 mm)	24 Watts	2 lb. / 910g
GRX-(GG-2700, 3000, 4000)-15D-1200	3" (75 mm)	15°	48" (1200 mm)	48 Watts	3.8 lb. / 1720g

GRX Series Specifications	
Voltage: 24VDC	
Current: 125mA Per LED	
Power: 3W Per LED	
IP Rating: 66	
CRI Value: 85	
Color	Output
2700K	150 Lm Per LED
3000K	160 Lm Per LED
4000K	180 Lm Per LED



To prevent scalloping, position the center of the fixture a minimum of 3" from the surface to be illuminated.



**TOKISTAR LIGHTING INC.**

1015 E. DISCOVERY LANE  
 ANAHEIM, CA 92801  
 TEL: 714 772 7005 FAX: 714 772 7014  
 email: info@tokistar.com Website: tokistar.com

Gradient GRX-GG Series Submittal	No.	Part	Material
Catalog#: GRX-GG-(2700K, 3000K, 4000K)-15D-XXXX	1	Extrusion	Anodized Aluminum
Date: November 1, 2017	2	Cover	Anodized Aluminum
Drawn By: R. Cordova	3	Mounting Bracket	SUS
Scale: 1:4	4	LED Lens	PC
	5	Power Cable	PVC Insulation (#18 AWG x 2 / # 22 AWG x 2)
	6	Power Cable	PVC Insulation (#18 AWG x 2)
	7	Connectors	Nylon (waterproof) with IP67 rating
	8	Glare Guard	Powder Coated Aluminum