


LS Series Tapelight with 0.4 Watt TOKILED[®]



CATALOG#	P (INCH)	MAX. LENGTH
LSW-15-(LED CODE)	0.6 ± .08	5 FT.
LSW-30-(LED CODE)	1.2 ± .08	10 FT.
LSW-50-(LED CODE)	2 ± .08	16 FT.
LSW-80-(LED CODE)	3 ± .12	25 FT.
LS(W,C,B)-100-(LED CODE)	4 ± .16	33 FT.
LS(W,C,B)-150-(LED CODE)	6 ± .20	50 FT.
LS(W,C,B)-300-(LED CODE)	12 ± .40	82 FT.

0.4 WATT TOKILED [®] 8VDC/50.0mA			
PART#	LED CODE	COLOR	LUMEN
TLED-WW-UB	WW-UB	2400K WHITE	7.0 Lm
TLED-IW-UB	IW-UB	3000K WHITE	10.0 Lm
TLED-WH-UB	WH-UB	6500K WHITE	12.0 Lm

LS CABLE COLOR CODE: W=WHITE, C=CLEAR, B=BROWN
CLEAR AND BROWN AVAILABLE IN 4", 6" AND 12" SPACING ONLY



TOKISTAR LIGHTING INC.

1561 N. GEMINI PL.
ANAHEIM, CA 92801
TEL: 714 772 7005 FAX: 714 772 7014
email: info@tokistar.com Website: tokistar.com

TAPELIGHT SERIES SUBMITTAL	NO.	PART	MATERIAL
CATALOG#: LS_--(LED CODE)	1	CABLE	PVC INSULATION WITH PLATED COPPER CONDUCTORS
DATE: NOVEMBER 3, 2008	2	LED	SOLID STATE LED
DRAWN BY: R. CORDOVA	3	LAMP SOCKET	POLYCARBONATE WITH PLATED COPPER CONTACTS
SCALE: 1:2	4	CAP	SILICONE (CLEAR)
WEIGHT: 31g/ft.	5	LEAD WIRE	PVC INSULATION WITH PLATED #12 AWG X 2
	6	CORD PROTECTOR	PVC
	7	END CAP	PVC