


# TDR CHASE-0.30 WATT TOKILEDS®



CATALOG#	P (INCH)	EXTRUSION LENGTH	MAX. FIXTURE LENGTH
TDR-2C-(LED CODE)	2 ± .08"	96.5"	32'
TDR-3C-(LED CODE)	3 ± .08"	96.5"	50'
TDR-4C-(LED CODE)	4 ± .08"	96.5"	60'

0.30 WATT TOKILEDS® 12VAC/25.0mA				
PART#	LED CODE	COLOR	LUMEN	WAVELENGTH
TLED-WW-HB	WW-HB	2400K WHITE	5.4Lm	589.5
TLED-IW-HB	IW-HB	3000K WHITE	6.7Lm	574.1
TLED-WH-HB	WH-HB	6500K WHITE	8.4Lm	480.1



**TOKISTAR LIGHTING INC.**  
 1015 E. DISCOVERY LANE  
 ANAHEIM, CA 92801  
 TEL: 714 772 7005 FAX: 714 772 7014  
 email: info@tokistar.com Website: tokistar.com

TDR CHASE SERIES SUBMITTAL	NO.	PART	MATERIAL
CATALOG#: TDR-_(LED CODE)	1	EXTRUSION COVER	PVC
DATE: OCTOBER 10, 2013	2	EXTRUSION BASE	PVC
DRAWN BY: R. CORDOVA	3	LED	SOLID STATE LED
SCALE: 1:2	4	LAMP SOCKET	POLYCARBONATE WITH PLATED COPPER CONTACTS
WEIGHT: 75g/FT. @ 2"O.C.	5	LEAD WIRE	PVC INSULATION WITH PLATED #18 AWG X 3
	6	END CAP (FEED END)	PVC
	7	END CAP (DEAD END)	PVC