



TLXWG-CH-FB/Wall Grazer w/Channel & Fixed Bracket

Maximum Channel Length = 94.625" (2.4 M)



Catalog #	Light Bar	Max. Length
TLXWG-CH-(2400, 2700, 3000)-FB	8 In. (200 mm)	94.625 In. / 2.4 M (12 Light Bars)

FB = Fixed Bracket

TokiLux Wall Grazer Specifications

Input Voltage: 24 VDC

Current: 167mA Per Light Bar

Power: 4.0 W Per Light Bar

LED Code	Color	Output	
2400	2400K	47.5 Lm Per Watt	285 Lm Per Ft.
2700	2700K	47.5 Lm Per Watt	285 Lm Per Ft.
3000	3000K	50.0 Lm Per Watt	300 Lm Per Ft.

Beam Spread: 18° X 48°



TOKISTAR LIGHTING INC.

1015 E. DISCOVERY LANE
ANAHEIM, CA 92801
TEL: 714 772 7005 FAX: 714 772 7014
email: info@tokistar.com Website: tokistar.com

TokiLux WG w/Channel & Fixed Bracket Submittal	No.	Part	Material
Catalog#: TLXWG-CH-(2400,2700,3000)-FB	1	Light Bar	Rigid Polycarbonate
Date: July 1, 2020	2	LED	Solid-State LED
Drawn By: R. Cordova	3	Rail	Rigid Polycarbonate
Scale: 1:2	4	Feed End	Rigid Polycarbonate
Weight: 183g/0.40 lb per ft.	5	End Cap	Rigid Polycarbonate
	6	Mounting Clamp	Polycarbonate
	7	Fixed Bracket	Aluminum
	8	Extrusion	Aluminum