


# TXRA CHASE-0.30 WATT TOKILEDDS®



CATALOG#	P (INCH)	EXTRUSION LENGTH	MAX. FIXTURE LENGTH
TXRA-2C-(LED CODE)	2 ± .08"	96.5"	32'
TXRA-3C-(LED CODE)	3 ± .08"	96.5"	50'
TXRA-4C-(LED CODE)	4 ± .08"	96.5"	60'

0.30 WATT TOKILEDDS® 12VAC/25.0mA				
PART#	LED CODE	COLOR	LUMEN	WAVELENGTH
TLED-WW-HB	WW-HB	2400K WHITE	5.4Lm	589.5
TLED-IW-HB	IW-HB	3000K WHITE	6.7Lm	574.1
TLED-WH-HB	WH-HB	6500K WHITE	8.4Lm	480.1



## TOKISTAR LIGHTING INC.

1015 E. DISCOVERY LANE  
ANAHEIM, CA 92801  
TEL: 714 772 7005 FAX: 714 772 7014  
email: info@tokistar.com Website: tokistar.com

### TXRA CHASE SERIES SUBMITTAL

	NO.	PART	MATERIAL
CATALOG#: TXRA-_(LED CODE)	1	EXTRUSION COVER	ANODIZED ALUMINUM
DATE: OCTOBER 10, 2013	2	EXTRUSION BASE	ANODIZED ALUMINUM
DRAWN BY: R. CORDOVA	3	LED	SOLID STATE LED
SCALE: 1:2	4	CAP	SILICONE (CLEAR)
WEIGHT: 80g/FT. @ 2" O.C.	5	LAMP SOCKET	POLYCARBONATE WITH PLATED COPPER CONTACTS
	6	LEAD WIRE	PVC INSULATION WITH PLATED #18 AWG X 3
	7	END CAP (FEED END)	PVC
	8	END CAP (DEAD END)	PVC